

IN THE CLAIMS:

1. (Currently Amended) A composite component comprising:
a capacitor element comprising at least one insulation layer
and at least two electrode layers;
a ~~spiral~~helical conductor strip located on at least an
external peripheral surface of said capacitor element, said
~~spiral~~helical conductor strip being in close contact with said
external peripheral surface; and
a plurality of terminals located on an external peripheral
surface of said composite component, wherein
said electrode layers and said helical~~spiral~~ conductor strip
are electrically connected to said plurality of terminals.
2. (Currently Amended) The composite component according to
claim 1, wherein said helical~~spiral~~ conductor strip is
constructed of a same material as the composite component
terminals.

Serial No.: 09/423,806

3. (Currently Amended) The composite component according to claim 1, wherein a helical~~spiral~~ axis of said helical~~spiral~~ conductor strip is parallel with said electrode layers.

4. (Previously Amended) The composite component according to claim 1, comprising a plurality of capacitors.

5. (Currently Amended) The composite component according to claim 1, wherein said helical~~spiral~~ conductor comprises two ends and a portion therebetween, and said helical~~spiral~~ conductor strip is electrically connected with said plurality of terminals at two ends and said portion.

6. (Currently Amended) The composite component according to claim 1, wherein said helical~~spiral~~ conductor strip and at least one of said electrode layers are electrically connected to one of said terminals.

Serial No.: 09/423,806

7. (Original) The composite component according to claim 1, wherein an entire surface thereof other than portions occupied by said terminals is covered by an external insulation layer.

8. (Previously Amended) The composite component according to claim 7, wherein said external insulation layer comprises magnetic material powder and/or ceramic powder.

9. (Original) The composite component according to claim 7, wherein said external insulation layer is covered with conductive material.

10. (Currently Amended) A composite component comprising:
a helical~~spiral~~ conductor strip located on a peripheral surface of a component body, said component body being an insulation body, said conductor being in close contact with said component body;

an insulation layer located on said conductor; and

Serial No.: 09/423,806

a capacitor comprising at least one capacitor insulation layer and at least two electrode layers, said capacitor being located on said insulation layer, wherein

a helicalspiral axis of said helicalspiral conductor strip is parallel with a plane of said electrode layers, and said electrode layers and said helicalspiral conductor strip are electrically connected.

11. (Currently Amended) A method of manufacturing a composite component comprising:

forming a capacitor comprising at least one insulation layer and at least two electrode layers;

forming an additional insulation layer on an external peripheral surface of said insulation layer and covering said capacitor; and

forming a helicalspiral conductor strip and a terminal on an external periphery of said covered capacitor.

Serial No.: 09/423,806

12. (Previously Amended) The method of manufacturing a composite component according to claim 11, wherein forming said conductor and said terminal comprises:

forming a conductive layer on the external periphery of said covered capacitor, and

laser machining said conductive layer.

13. (Previously Amended) The method of manufacturing a composite component according to claim 11, wherein forming said conductor and said terminal comprises:

forming a conductive layer on the external periphery of said covered capacitor, and

machine-cutting said conductive layer.

14. (Previously Amended) The method of manufacturing a composite component according to claim 11, wherein forming said conductor and said terminal comprises:

forming a conductive layer on the external periphery of said covered capacitor, and

wet-etching said conductive layer.

Serial No.: 09/423,806

15. (Currently Amended) The method of manufacturing a composite component according to claim 11, wherein forming said conductor and said terminal comprises:

covering with a mask a surface portion other than surface areas where said terminals and said helical~~spiral~~ conductor strip are formed on the peripheral surface of said covered capacitor, and

forming a conductor on said surface areas not covered by said mask.

16. (Previously Amended) The method of manufacturing a composite component according to claim 15, wherein forming a conductor comprises vacuum-plating or wet-plating.

17. (Currently Amended) The method of manufacturing a composite component according to claim 11, wherein forming said conductor and said terminal comprises:

forming a conductor with conductive paste on surface areas where said terminals and said helical~~spiral~~ conductor strip are formed on the external periphery of said covered capacitor, and

Serial No.: 09/423,806

forming a plated layer on the conductor formed by said conductive paste.

18. (Currently Amended) A method of manufacturing a composite component comprising:

forming a capacitor comprising at least one insulation layer and at least two electrode layers located on a portion of said insulation layer;

forming an additional insulation layer on an external peripheral surface of said insulation layer and said capacitor; and

forming a helical~~spiral~~ conductor strip and a terminal on an external periphery of said additional insulation layer.

19. (Currently Amended) A method of manufacturing a composite component comprising:

forming a capacitor comprising at least one insulation layer and at least two electrode layers;

Serial No.: 09/423,806

forming a helical~~spiral~~ conductor strip in close contact with an external periphery of a component body, said component body being an insulation body; and

laminating said capacitor and said component body, on which said helical~~spiral~~ strip of conductor is closely formed, via another insulation layer located therebetween.

20. (Previously Added) The composite component according to claim 10, wherein the component body comprises a magnetic body.

21. (Currently Amended) The method of manufacturing a composite component according to claim 19, wherein the component body comprises a magnetic body.